

www.xcoatnano.com

X-Coat™ Nano HS

Extreme Performance Coating
Patented Nano-Zinc Technology

U.S. Patent No. 8,236,903

Features

- Incorporates our patented nano-zinc technology for more thorough and denser cross-linking of finish.
- Nano-zinc cross-linking provides superior:
 - Lay-down gloss
 - Durability
 - Soil resistance
 - Gloss build
 - Mark resistance
 - Dry and recoat times
- Ammonia-free for dramatically reduced odor.
- High solids formula offers greater protection with fewer coats.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low emissions formula – meets California's new 1% VOC Regulation.
- Fast-drying – 15-20 minutes under normal conditions (50% humidity and 70°F) between coats.
- Slip-resistant – UL-classified

NANO
technology

Properties

Type	Acrylic Emulsion
Form	Opaque Liquid
Odor.....	Bland
Color.....	Milky White
Film Clarity	Clear
Weight per Gallon.....	8.65 Lbs.
pH	8.0 – 8.5
Floor Solids.....	25%
Storage Stability	Min. 1 Year
Freeze/Thaw.....	Protect From Freezing
V.O.C.	0.75%

* Properties are typical and subject to usual manufacturing tolerances.



89FF



ESSENTIAL®
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com