

[www.xcoatnano.com](http://www.xcoatnano.com)

# X-Coat™ Nano

## Extreme Performance Coating

### Patented Nano-Zinc Technology

U.S. Patent No. 8,236,903

### Features

- Incorporates our patented nano-zinc technology for more thorough and denser cross-linking of finish.
- Nano-zinc cross-linking provides superior:
  - Lay-down gloss
  - Durability
  - Soil resistance
  - Gloss build
  - Mark resistance
  - Dry and recoat times
- Ammonia-free for dramatically reduced odor.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low emissions formula – meets California's new 1% VOC Regulation.
- Fast-drying – 20 minutes under normal conditions.
- Slip-resistant – UL-classified

**NANO**  
technology

### Properties

Type .....	Acrylic Emulsion
Form .....	Opaque Liquid
Odor.....	Bland
Color.....	Milky White
Film Clarity .....	Clear
Weight per Gallon.....	8.57 Lbs.
pH .....	8.0 – 8.5
Floor Solids.....	20%
Storage Stability .....	Min. 1 Year
Freeze/Thaw.....	Protect From Freezing
V.O.C. ....	0.59%

\* Properties are typical and subject to usual manufacturing tolerances.



88FF



**ESSENTIAL®**  
**INDUSTRIES**

P.O. Box 12  
Merton, Wisconsin 53056  
Phone: (262) 538-1122  
[www.essind.com](http://www.essind.com)